

# EBM

Coatings and Chemicals

## Technical Data Sheet

### **EBM** EM Wood and Wall Putty

EM5000

**Description :** A ready-mixed water based filler putty based on Poly Vinyl Acetate Special fine powders and Linseed oil for interior wood and cement Surfaces such as doors, frames, walls, ceiling and gypsum boards.

#### **Features:**

1. Ease of application
2. Easy sanding
3. Excellent filling properties
4. No sagging at high film thickness
5. Excellent coverage to minor substrate defects
6. Eliminate surface imperfections

#### **Physicals Properties:**

Viscosity (Rot thinner at 25 <sup>0</sup> C)	:	160 - 180 poise
Finish	:	Matt
Flash Point	:	Not applicable
Specific Gravity	:	1.75 kg/L
Solid by Weight	:	52 ± 2
Coverage rate	:	0.5 – 1.0kg/m <sup>2</sup> depends on the surface
Dry film thickness	:	maximum 1mm
Shelf Life (dry and cool store)	:	One year

#### **Surface Preparation and Application Method:**

1. The surface should be dry, free from dirt, oil, grease and powdery material.
2. Sand the entire surface and remove the dust.
3. Wash the surface with clean water and allow completing dry.
4. Apply one coat of **EBM** EM Exterior Latex Sealer or **EBM** EM Int. & Ext. Primer Sealer.
5. Apply 1 -2 coats of **EBM** EM Wood & Wall Putty.
6. After drying, sand the surface completely and remove the dust.

**Doha Factory for Paints and Chemicals**

Tel-44504119 - Fax: 44510566 - P.O.Box:35409. New Industrial Area-Doha Qatar

E-mail: [info@dohapaints.com](mailto:info@dohapaints.com). [www.dohapaints.com](http://www.dohapaints.com)

# EBM

Coatings and Chemicals

## Technical Data Sheet

### **EBM EM Wood and Wall Putty**

**EM5000**

#### **Dilution and Application:**

Type of thinner	:	Nothing required (ready to use)
Tools	:	Trowel, spatula, putty knife

#### **Drying time (at 25<sup>0</sup>C):**

Touch dry	:	1 – 2 hours
Hard dry	:	3 – 4 hours

Next coat can be applied after 4 hours.

#### **Subsequent Coats:**

<b>EBM EN Synthetic Undercoat</b>	<b>EBM EM Gloss Emulsion</b>
<b>EBM EM Exterior Acrylic Emulsion</b>	<b>EBM EM Semi-Gloss Emulsion</b>
<b>EBM EM Int. &amp; Ext. Primer Sealer</b>	<b>EBM EM Eggshell Emulsion</b>
<b>EBM EM Exterior Latex Sealer</b>	

**Colors:** White

**Packing:** 25 kg/drum, 20kg/drum, 4kg/gallon

#### **Remarks:**

Before Application

- Stir well
- Check Temperature above 5<sup>0</sup>C and relative humidity less than 85%

After Application

- Clean all tools used immediately with water
- Close the cans after used
- Store in dry and cool area

For more information, don't hesitate to contact our Technical Department.

**Doha Factory for Paints and Chemicals**

**Tel-44504119 - Fax: 44510566 - P.O.Box:35409. New Industrial Area-Doha Qatar**

**E-mail: info@dohapaints.com. www.dohapaints.com**