

EBM

Coatings and Chemicals

Technical Data Sheet

EBM TX Texture Coating

TX4000
Fine Tex

TX4001
Medium Tex

TX4002
Coarse Tex

Description : A high build decorative textured finish based on Acrylic co-polymer And different sizes of calcium carbonates aggregates, for interior and Exterior applications on masonry, concrete panels walls, ceiling and Gypsum boards.

Features:

1. High permeability
2. High film thickness
3. Different patterns
4. No sagging at high film thickness
5. Excellent coverage to minor substrate defects

Physicals Properties:

Viscosity (Rot thinner at 25 ⁰ C)	:	160 - 180 poise
Finish	:	Matt
Flash Point	:	Not applicable
Specific Gravity	:	1.80 kg/L
Solid by Weight	:	76 ± 2
Coverage rate	:	0.5 – 1.5kg/m ² depends on type of texture Pattern and method of application
Dry film thickness	:	Depends on method of application and Required style
Shelf Life (dry and cool store)	:	One year

Surface Preparation and Application Method:

1. The surface should be dry, free from dirt, oil, grease and powdery material.
2. For old painting, remove the old paint as much as possible.
3. Wash the surface with diluted Ammonia Solution.
4. For new surfaces sand the entire surface and remove the dust.
5. Wash the surface with clean water and allow completing dry.
6. Apply one coat of **EBM EM Exterior Latex Sealer** or **EBM EM Int. & Ext. Primer Sealer**.
7. Apply 1-2 coats of **EBM EM wood and wall putty**.
8. Apply one coat of **EBM TX Texture Coating**.

Doha Factory for Paints and Chemicals

Tel-44504119 - Fax: 44510566 - P.O.Box:35409. New Industrial Area-Doha Qatar

E-mail: info@dohapaints.com. www.dohapaints.com

EBM

Coatings and Chemicals

Technical Data Sheet

EBM TX Texture Coating

TX4000
Fine Tex

TX4001
Medium Tex

TX4002
Coarse Tex

Dilution and Application:

Type of thinner	:	Clean water
Percentage of thinning	:	0 - 5% by volume
Tools	:	Special Roller and Hopper Gun Airspray

Drying time (at 25⁰C):

Touch dry	:	2 – 3 hours
Hard dry	:	10 – 12 hours
A second coat can be applied after 24 hours		

Subsequent Coats:

EBM EM Gloss Emulsion	EBM EM Vinyl Silk Emulsion
EBM EM Semi-gloss Emulsion	EBM EM Int. and Ext. Emulsion
EBM EM Egg Shell Emulsion	EBM AC Acrylic-Poly Urethane Top Coat 2k

Colors: White

Packing: 25 kg/drum

Remarks:

Before Application

- Stir thoroughly
- Check Temperature above 5⁰C and relative humidity less than 85%

After Application

- Clean all tools used immediately with water
- Close the cans after used
- Store in dry and cool area

For more information, don't hesitate to contact our Technical Department.

Doha Factory for Paints and Chemicals

Tel-44504119 - Fax: 44510566 - P.O.Box:35409. New Industrial Area-Doha Qatar

E-mail: info@dohapaints.com. www.dohapaints.com