

## Technical Data Sheet

### **EBM NC Wood Putty Clear**

**NC5000**

**Description :** A Nitrocellulose Transparent filler for all types of Wood and can be used as first coat sanding sealer by trowel or special knife.

#### **Features:**

1. Hi filling power
2. Fine and smooth finish
3. One coat application
4. Easy Sanding

#### **Physicals Properties:**

Viscosity (Rot thinner at 25 <sup>0</sup> C)	:	220 - 240 POISE
Finish	:	Silk
Flash Point	:	16 <sup>0</sup> C
Specific Gravity	:	1.5 ± 0.02 kg/L
Solid by Weight	:	65% ± 2
Coverage rate	:	3 - 4m <sup>2</sup> /Liter
Dry film thickness	:	200 micron
Shelf Life (dry and cool store)	:	One year

#### **Surface Preparation and Application Method:**

1. The surface should be dry, free from dirt, oil, grease and powdery material.
2. Sand the entire surface until completely smooth.
3. Apply one coat of **EBM NC Wood Putty Clear** by trowel or knife.
4. After drying, sand the surface until completely smooth.

# EBM

Coatings and Chemicals

## Technical Data Sheet

**EBM NC Wood Putty Clear**

NC5000

### Dilution and Application:

Type of thinner	:	No thinning required
Tools	:	Trowel, knifing putty

### Drying time (at 30°C):

Touch dry	:	50 - 60 minutes
Hard dry	:	80 - 100 minutes
Sandable	:	2 hours

### Subsequent Coats:

EBM NC Sanding Sealer  
EBM NC Lacquer Clear (Matt, 10% Gloss, 30% Gloss, semi-gloss, full gloss)

Colors:      Transparent

Packing:    3.5 Liter Gallon, One Litter Can

### Remarks:

Before Application

- Stir thoroughly
- Check Temperature above 5°C and relative humidity less than 85%

After Application

- Clean all tools used immediately with TH 250 Thinner
- Close the cans after used
- Store in dry and cool area

For more information, don't hesitate to contact our Technical Department.